



The Good Stuff

- **Rigid delivery, to the last drop**
Rigid polypropylene that won't kink or curl, and a side-hole suction foot that draws chemistry to the very bottom
- **Universal drum compatibility**
Fits both fine and buttress drum openings with tool-free depth adjustment
- **Three lengths, one solution**
Available in 33, 48, and 54 inches to fit virtually any drum or tote depth

Features

- Made with chemical resistant polypropylene
- Fits both 2 in. NPS and buttress drum threads
- Vent hole prevents vacuum pressure buildup
- 3/4 in. inside diameter pipe for high-volume pumping
- Rigid construction eliminates hose kinking
- Three hose barbs included: 1/4, 3/8, and 1/2 inch
- Chemical resistant check valve to prevent backflow
- Hastelloy mesh strainer
- Suction foot maintains draw at drum floor

Options

- Lance length
 - 33 in. (0.8 m)
 - 48 in. (1.2 m)
 - 54 in. (1.4 m)

Specifications

- Lance length/diameter.....33 in. (0.8 m), 48 in. (1.2 m), 54 in. (1.4 m)
with 3/4 in. (19.1 mm) diameter
- Drum Depth MountingDLV-33 max drum depth of 35.9 in.
DLV-48 max drum depth of 50.5 in.
DLV-54 max drum depth of 56.5 in.
- Thread type2 in. NPS and 2 in. buttress threads
- Fitting sizes1/4, 3/8, and 1/2 inch hose barbs included
- Seal Type EPDM or Viton

Requirements

- Liquid temperature range..... 40-100 °F (4.4-37.8 °C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

Industries

- Food and Beverage
- Agriculture
- Industrial



How to Buy

